



Features:

- Highly developed 10 pin radial tumbler lock insert.
- Lock bolt diameter 25.4mm (1 inch) case hardened to 60 rockwell hardness (746 VPN), crop, drill and saw resistant.
- Anti drill centre pin on radial pin tumbler lock.
- Drill resistant lock cover to prevent hollow core drilling of lock.
- 10mm diameter steel ball bearings operated by internal cam mechanism.
- Lock face design is resistant to attack by slide hammer (dent puller) devices.
- Bulldog Super Lock Bolt has been used in many applications of security products that have passed independent attack test including SCM Road Vehicle Research Institute, and Sold Secure.
- Resistant to attack by punches or drifts due to internal lock chamber design.
- Keys can only be removed in locked position, no possibility of accidental locking.
- 2 keys supplied with lock as standard. Multiple locks can be supplied with same key for fleet or multi user applications.

<u>Item</u>	<u>Overall Length</u>	<u>Description</u>
SA1	L = 158mm	Standard Lock Bar c/w Cup
SA1C	L= 175mm	Commercial Lock Bar c/w Cup
SA1CS	L= 175mm	Commercial Lock Bar for AW c/w Short Cup
SA1AJ	L = 139mm	Lock Bolt for AJ10
SA2	L = 125mm	Lock Bolt (no cup)
SA3	L= 60mm	Lock Bolt with spacers for Titan, Centaur, AI20, GA90 and TE100
CT60A	L = 60mm	Lock Bolt for CT440