



Features:

- Highly developed 10 pin radial tumbler lock insert.
- Lock bolt diameter 25.4mm (1 inch) case hardened to 60 rockwell hardness (746 VPN), crop, drill and saw resistant.
- Anti drill centre pin on radial pin tumbler lock.
- Drill resistant lock cover to prevent hollow core drilling of lock.
- 10mm diameter steel ball bearings operated by internal cam mechanism.
- Lock face design is resistant to attack by slide hammer (dent puller) devices.
- Bulldog Super Lock Bolt has been used in many applications of security products that have passed independent attack test including SCM Road Vehicle Research Institute, and Sold Secure.
- Resistant to attack by punches or drifts due to internal lock chamber design.
- Keys can only be removed in locked position, no possibility of accidental locking.
- 2 keys supplied with lock as standard. Multiple locks can be supplied with same key for fleet or multi user applications.

| <u>Item</u> | <u>Overall Length</u> | <u>Description</u> |
|--------------|-----------------------|--|
| SA1 | L = 158mm | Standard Lock Bar c/w Cup |
| SA1C | L = 175mm | Commercial Lock Bar c/w Cup |
| SA1CS | L = 175mm | Commercial Lock Bar for AW c/w Short Cup |
| SA1AJ | L = 139mm | Lock Bolt for AJ10 |
| SA2 | L = 125mm | Lock Bolt (no cup) |
| SA3 | L = 60mm | Lock Bolt with spacers for Titan, Centaur, AI20, GA90 and TE100. Under the head 41mm or 31mm with spacers |
| CT60A | L = 60mm | Lock Bolt for CT440 |