

# TRAILCLAMP RANGE

Please note this wheel clamp is not suitable for alloy wheels.

| MODEL  | Fits Wheels/Tyres   | Typical Applications | Product Weight |
|--------|---|----------------------|----------------|
| TC100  | 4.80/4.00 x 8 (4PR Load Range)  | Trailers             | 6.6kg          |
| TC100X | 4.80/4.00 x 8 (6PR Load Range)  | Trailers             | 6.6kg          |
| TC150  | 16.5 x 6.5 - 8  | Trailers             | 6.9kg          |
| TC200  | 5.00 x 10, 5.20 x 10, 145 x 10  | Trailers             | 7.3kg          |
| TC250  | 155/70 R12 (suitable for 155/70 R12 Heavy duty tyres fitted to twin wheel lfor Williams Car Transporters which measure 170mm in width (for normal 155/70 R12 applications see QD11) | Car Transporter      | 8.1kg          |
| TC300  | 20.5 x 8 - 10   | Trailers             | 8.0kg          |
| TC350  | 195/55/ R10   | Trailers             | 8.0kg          |
| TC355  | 195/55/ R10 (Eternity Tyre)   | Trailers             | 8.0kg          |
| TC400  | 145/70 R13 ST3000   | Trailers             | 9.0kg          |
| TC450  | 145/70 R13 ST4000   | Trailers             | 9.0kg          |



## BULLDOG SECURITY PRODUCTS LIMITED

Units 1 - 4 Stretton Road, Much Wenlock, Shropshire, TF13 6DH. Tel: 01952 728171 sales@bulldogsecure.com www.bulldogsecure.com