



Features:

- Simple to use, only two parts to clamp.
- No pre-assembly required.
- Comes complete with Bulldog's Plunge Lock which can be locked without the use of the key.
- 10 pin drill and pick resistant lock with over a million possible key combinations.
- Main arm constructed from 75 x 6mm rolled edge steel.
- 11" (270mm) diameter wheel nut protection disc 3mm thick.
- Models available:-
 - TC100: To fit tyres 4.80/4.00 x 8" (4PR Load Range)
 - TC100X: To fit tyres 4.80/4.00 x 8" (6PR Load Range)
 - TC150: To fit tyres 16.5 x 6.5 - 8"
 - TC200: To fit tyres 5.00 x 10" 5.20 x 10" 145 x 10"
 - TC250: Fits 155/70 R12 (**suitable for 155/70 R12 heavy duty tyres fitted to twin wheel
If for Williams Car Transporters which measure 170mm in width (For normal 155/70 R12
Applications see QD11).**)
 - TC300: To fit tyres 20.5 x 8 - 10" steel wheel
 - TC320: To fit tyres 20.5 x 8 - 10" alloy wheel
 - TC350: To fit tyres 195/55 R10
 - TC355 To fit tyres 195/55 R10 (Eternity Tyre)
 - TC400: To fit tyres 145/70 R13 ST3000
 - TC450: To fit tyres 145/70 R13 ST4000

Please note this wheel clamp is not suitable for alloy wheels.

- Weight TC100 = 6.6kg TC100X=6.6kg TC150 = 7.5kg TC200 = 8.3kg TC250 = 8.1kg
 TC300 = 8.0kg TC320 = 8kg TC350 = 8kg TC400= 9.0kg TC450=9.0kg