

TRAILCLAMP RANGE

Please note this wheel clamp is not suitable for alloy wheels.

| MODEL | Fits Wheels/Tyres | Typical Applications | Product Weight |
|--------|---|----------------------|----------------|
| TC100 | 4.80/4.00 x 8 (4PR Load Range) | Trailers | 6.6kg |
| TC100X | 4.80/4.00 x 8 (6PR Load Range) | Trailers | 6.6kg |
| TC150 | 16.5 x 6.5 - 8 | Trailers | 6.9kg |
| TC200 | 5.00 x 10, 5.20 x 10, 145 x 10 | Trailers | 7.3kg |
| TC250 | 155/70 R12 (suitable for 155/70 R12 Heavy duty tyres fitted to twin wheel lfor Williams Car Transporters which measure 170mm in width (for normal 155/70 R12 applications see QD11) | Car Transporter | 8.1kg |
| TC300 | 20.5 x 8 - 10 steel wheel | Trailers | 8.0kg |
| TC320 | 20.5 x 8 - 10 alloy wheel | Trailers | 8.0kg |
| TC350 | 195/55/ R10 | Trailers | 8.0kg |
| TC355 | 195/55/ R10 (Eternity Tyre) | Trailers | 8.0kg |
| TC400 | 145/70 R13 ST3000 | Trailers | 9.0kg |
| TC450 | 145/70 R13 ST4000 | Trailers | 9.0kg |



BULLDOG SECURITY PRODUCTS LIMITED

Units 1 - 4 Stretton Road, Much Wenlock, Shropshire, TF13 6DH. Tel: 01952 728171 sales@bulldogsecure.com www.bulldogsecure.com